

R410A CLASSIC FIXED SPEED COOLING ONLY SYSTEMS


Nominal Cooling (Kw)	
Nominal Heating (Kw)	
UK Cooling (Kw)	
UK Heating (Kw)	
Nominal Sensible Cooling (Kw)	
Sensible Heat Ratio (nominal)	
Electrical Supply	
EER (nominal)	
Energy Label	
Starting Current (A)	
Running Current (A)	
Fuse Rating	
Interconnecting Cable	
Pipe Size Gas	
Pipe Size Liquid	
Max Pipe Length / Height (m)	
Noise Level (dBA)	
Weight (Kg)	
DIMENSIONS	
Width	
Depth	
Height	
Charge R410A (kg) - 7m	

WALL MOUNTED							
Indoor	Outdoor	Indoor	Outdoor	Indoor	Outdoor	Indoor	Outdoor
<i>MSC-GA25VB</i>	<i>MUH-GA25VB</i>	<i>MSC-GA35VB</i>	<i>MUH-GA35VB</i>	<i>MSH-GA50VB</i>	<i>MUH-GA50VB</i>	<i>MSH-GB60VA</i>	<i>MUH-GB60VA</i>
2.5		3.45		5.0		6.5	
-		-		-		-	
2.5		3.4		4.95		6.45	
-		-		-		-	
1.75		2.28		3.25		4.1	
0.7		0.66		0.65		0.63	
220-240v, 50Hz		220-240v, 50Hz		220-240v, 50Hz		220-240v, 50Hz	
3.23		3.08		2.76		2.62	
A		B		D		D	
-	21	-	21	-	37	-	74
0.17	3.23	0.19	4.83	0.3	7.9	0.3	10.82
6	16	6	16	6	16	6	20
2 Core 12v		2 Core 12v		2 Core 12v		2 Core 12v	
3/8"		3/8"		1/2"		5/8"	
1/4"		1/4"		1/4"		1/4"	
20 / 10		25 / 10		25 / 10		25 / 10	
25 - 36	45	26 - 40	49	34 - 42	52	37 - 45	53
9	31	10	30	16	44	16	60
815	800	815	800	1100	850	1100	840
244	285	244	285	258	290	258	290
278	550	278	550	325	605	325	605
0.6		0.75		1.45		2	

Indoor and outdoor units require separate 240v, 50hz single phase supply.
 Indoor and outdoor units are connected via a 2 core low voltage cable.

R410A CLASSIC FIXED SPEED HEAT PUMP SYSTEMS


Nominal Cooling (Kw)	
Nominal Heating (Kw)	
UK Cooling (Kw)	
UK Heating (Kw)	
Nominal Sensible Cooling (Kw)	
Sensible Heat Ratio (nominal)	
Electrical Supply	
COP / EER (nominal)	
Energy Label	
Starting Current (A)	
Running Current (A)	
Fuse Rating	
Interconnecting Cable	
Pipe Size Gas	
Pipe Size Liquid	
Max Pipe Length / Height (m)	
Noise Level (dBA)	
Weight (Kg)	
DIMENSIONS	
Width	
Depth	
Height	
Charge R410A (kg) - 7m	

WALL MOUNTED							
Indoor	Outdoor	Indoor	Outdoor	Indoor	Outdoor	Indoor	Outdoor
MSC-GA25VB	MUH-GA25VB	MSC-GA35VB	MUH-GA35VB	MSH-GA50VB	MUH-GA50VB	MSH-GB60VA	MUH-GB60VA
2.65		3.5		5.0		6.3	
3.0		3.7		5.2		7.2	
2.65		3.45		4.95		6.25	
2.5		3.05		4.3		6.0	
1.86		2.31		3.25		4.03	
0.7		0.66		0.65		0.64	
220-240v, 50Hz		220-240v, 50Hz		220-240v, 50Hz		220-240v, 50Hz	
3.66 / 3.23		3.63 / 3.21		3.23 / 2.81		2.90 / 2.61	
A / A		A / A		C / C		D / D	
-	22	-	27	-	37	-	74
0.17	3.43	0.19	4.65	0.3	7.93	0.3	10.7
6	16	6	16	6	16	6	20
2 Core 12v		2 Core 12v		2 Core 12v		2 Core 12v	
3/8"		3/8"		1/2"		5/8"	
1/4"		1/4"		1/4"		1/4"	
20 / 10		25 / 10		25 / 10		25 / 10	
25 - 39	49	26 - 40	49	34 - 42	52	34 - 45	53
9	32	10	35	16	47	16	74
815	800	815	800	1100	850	1100	840
244	285	244	285	258	290	258	330
278	550	278	550	325	605	325	850
0.8		0.8		1.8		2.35	

Indoor and outdoor units require separate 240v, 50hz single phase supply.
 Indoor and outdoor units are connected via a 2 core low voltage cable.